

ENSEKI Cooling Units



KX-18



KX-25



KX-32



KX-50



Specifications of 18L / 32L / 42L Cooling Units				
Model No.	KX-18	KX-25	KX-32	KX-50
Applicable Refrigerator Model	FA-1000 / XC -18	XC-25	XC-30 / XC -32	XC -42
Capacity	18L	25L	30L / 32L	42L
Dimensions (mm)	200(L)*280(W) *420(H)	190(L)*280(W) *440(H)	190(L)*380(W) *450(H)	190(L)*380(W) *530(H)
Voltage & Frequency	AC220V / 50Hz as standard DC12V available	AC220V / 50Hz as standard	AC 220V / 50Hz as standard	AC220V / 50Hz as standard
Input Power	65W	65W	65W	65W
Material	Welded Steel Tube	Welded Steel Tube	Welded Steel Tube	Welded Steel Tube
Delta T	35 °C (Coldest Point)	35 °C (Coldest Point)	40 °C (Coldest Point)	40 °C (Coldest Point)
Coolant	R717	R717	R717	R717



POWER UP YOUR LIFE

AOYAGI (H.K.) LTD.

Unit A, 5/F., Lladro Center, No. 72 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.
 Tel: (852) 2368 0021 Fax: (852) 2368 2011 E-mail: info@aoyagihk.com.hk
 Website: <http://www.aoyagihk.com.hk>